

Hardee Rear discharge Finish Mowers are supported by 4 swivel solid rubber tires with bearings. Floating 3 point linkage and Cat. 1 hitch pins. Seven (7) gauge reinforced mower deck, 3 cast hubs with spindle shafts, greased from top for easy service. Two (2) heavy duty reinforced belts, heavy duty balanced steel pulleys, heavy duty shielded PTO shaft (1 3/8" ASAE Cat.3 hitch pins), stamped steel wheel yokes, high blade tip speed, with precise blade overlap. Also equipped with rear chain guard protection.



Standard Features & Specifications

	RD-60	RD-72
MOWING WIDTH	58 1/8"	71 7/16"
OVERALL WIDTH	60 1/4"	73 3/4"
OVERALL LENGTH	51 1/4"	57 3/4"
WEIGHT	465 LBS.	500 LBS.
TRACTOR HP	17-40	23-40
BLADE TIP SPEED	15,770 FPM	16,821 FPM
BLADE OVERLAP	1 11/16"	2 1/16"

	BOTH SIZES
HEIGHT RANGE	1" to 5"
BLADES	Three Uplift 5/16" x 2"
SIDE SKIRTS	5/32" x 4"
FULLY SHIELDED	Driveline, Gearbox and Drive Belts
RPM	540
GEARBOX	30 HP
BELTS	"B"

****PLEASE CONTACT LOCAL DEALER FOR MORE INFORMATION****

4895 Red Bluff Road, Loris SC 29569
www.hardeebyevh.com

Phone: (843)756-2555 Fax: (843)756-4436
evhmfg@hardeebyevh.com