



STANDARD FEATURES

- 90 HP rated side gear boxes
- 2" output shaft
- Heavy-duty slip clutch
- Round blade holders
- Smooth top for easy cleaning
- Heavy-duty transfer gear box
- Shielded drive shaft
- Shock absorbers in drive lines
- Free swinging uplift blades
- Replaceable skid plates (3/8" x 3")
- Front and rear rubber shielding

LIFT TYPE

- Heavy Duty 3-point hitch – Cat. 2 & 3
- Floating linkage
- Two heavy-duty full caster bearing equipped tail wheels with grease fittings
- 5.00 X 8 puncture proof tires

SPECIFICATIONS

- Overall Width:.....133"
- Overall Length: Lift Type.....112"
Pull Type.....143"
- Cutting Width:.....126"
- Cutting Height:.....1-1/4" – 12"
- Cutting Capacity:Brush up to 2"
- Blades:.....1/2" X 3-1/2"
- Deck:.....7 ga.
- Gear Boxes.....540 RPM
- Net Weight: Lift Type.....2,170 lbs.
Pull Type.....2,460 lbs.

PULL TYPE

- Self-leveling hitch
- Parking stands and jack
- Ratchet type adjustment for cutting height 15" wheel (less tires)
- Bearing-equipped heavy-duty tail wheel hubs with grease fittings
- Pillow block on main drive shaft

<u>OPTIONS</u>	<u>ACCESSORIES</u>
Front & Rear Chain Guards	Hydraulic cylinder for height adjustment
Quick attach hitch Cat. 2 & 3 – Lift Type Only	Constant velocity drive shaft – Pull Type only
	Air Tires (15") – Pull Type only
	Puncture proof tires (6.00 X 9) – Pull Type only

****PLEASE CONTACT LOCAL DEALER FOR MORE INFORMATION****

4895 Red Bluff Road, Loris SC 29569
www.hardeebyevh.com

Phone: (843)756-2555 Fax: (843)756-4436
evhmfg@hardeebyevh.com

REVISED 10/9/2015