

The "Tiger" Red-Wing Heavy Duty Mowers, designed and built by Hardee by EVH, give you a choice of 4 different heavy duty gearboxes with 2" output shafts. They have round blade carriers with free-swinging blades, shielded "Slip Clutch" drive and replaceable skid shoes. Equipped with heavy duty "Self Leveling" type Hitch with swivel clevis, adds ease and convenience. Stroke control blocks come on center lift cylinder for depth precision. Hydraulic wing lift cylinders and transport locks for wing(s). Springs on all Wheels. All Hardee by EVH Mowers come standard with rubber shielding (front and rear).

T-9510-PTW

CUTTING WIDTH	10'
OVERALL WIDTH	10' 10"
OVERALL LENGTH	14' 10"
TRANSPORT WIDTH	8' 2"
MAX. TOTAL WEIGHT	3,950 lbs.
TONGUE WEIGHT	1,450 lbs.
TRACTOR HP	65 – 100 HP
BLADE TIP SPEED	13,625 – 14,280 FT/MIN
BLADE SIZE	½" X 3 ½" with 6" OVERLAP
WING FOLD	90° UP – 27° DOWN



T-9515-PTW

CUTTING WIDTH	15'
OVERALL WIDTH	15' 7" – TWO WINGS
OVERALL LENGTH	14' 10"
TRANSPORT WIDTH	8' 2"
MAX. TOTAL WEIGHT	4,850 lbs.
TONGUE WEIGHT	1,450 lbs.
TRACTOR HP	85 – 150 HP
BLADE TIP SPEED	13,625 – 14,280 FT/MIN
BLADE SIZE	½" X 3 ½" with 6" OVERLAP
WING FOLD	90° UP – 27° DOWN

Both are constructed of 7 gauge steel with a smooth top for easy cleaning. Blade bolt access in deck. Sturdy "Piano" hinged wing sections. They have 4" X 8" Hydraulic cylinder on center section with 3" X 17" Hydraulic cylinders to lift wings. Independent wing controls for the T-9515-PTW. You must choose your Hose set up, Gearbox and Driveshaft to complete mower for your tractor.

Item choices for completing machinery and available options are listed on the back of this page.

****PLEASE CONTACT LOCAL DEALER FOR MORE INFORMATION.****

4895 Red Bluff Road, Loris SC 29569
www.hardeebyevh.com

Phone: (843)756-2555 Fax: (843)756-4436
evhmfg@hardeebyevh.com

T-9510-PTW

T-9515-PTW



***** MUST CHOOSE ONE FROM EACH CATEGORY TO COMPLETE MOWER *****

T-9510-PTW

T-9515-PTW

HEIGHT AND WING CONTROL:

2 set of hoses (without Quick Connect Couplers) for direct coupling to tractor remotes. (2 tractor remote sets required)

HEIGHT AND WING CONTROL:

3 set of hoses (without Quick Connect Couplers) for direct coupling to tractor remotes. (3 tractor remote sets required)

WINGS INDEPENDENT

2 set of hoses (without Quick Connect Couplers) for direct coupling to tractor. (2 tractor remote sets required)

WINGS PLUMBED TOGETHER

GEARBOXES:

90 HP, 540 RPM

90 HP, 1,000 RPM

125 HP, 540 RPM

125 HP, 1,000 RPM

GEARBOXES:

90 HP, 540RPM

90 HP, 1,000 RPM

125 HP, 540 RPM

125 HP, 1,000 RPM

DRIVESHAFTS:

540 RPM – 1 ^{3/8}” 6 Spline

1,000 RPM – 1 ^{3/8}” 21 Spline

Constant Velocity 540 RPM – 1 ^{3/8}” 6 Spline

Constant Velocity 1,000 RPM – 1 ^{3/8}” CAT. 6

Constant Velocity 1,000 RPM – 1 ^{3/4}” CAT. 6

DRIVESHAFTS:

540 RPM – 1 ^{3/8}” 6 Spline

1,000 RPM – 1 ^{3/8}” 21 Spline

Constant Velocity 540 RPM – 1 ^{3/8}” 6 Spline

Constant Velocity 1,000 RPM – 1 ^{3/8}” CAT. 6

Constant Velocity 1,000 RPM – 1 ^{3/4}” CAT. 6

WHEELS:

6.00 X 9, Laminated Tires, 5 on 5 1/2, Set of 3

6.00 X 9, Laminated Tires, 5 on 5 1/2, Set of 5

Airplane Tires, 5 on 5 1/2, Set of 5

WHEELS:

6.00 X 9, Laminated Tires, 5 on 5 1/2, Set of 4

6.00 X 9, Laminated Tires, 5 on 5 1/2, Set of 6

Airplane Tires, 5 on 5 1/2, Set of 6

***** OPTIONS *****

SINGLE CHAIN GUARDS:

Front Chain Guards – Two Section Mower

Rear Chain Guards – Two Section Mower

DOUBLE CHAIN GUARDS:

Front Double Chain Guards Complete

Rear Double Chain Guards Complete

SINGLE CHAIN GUARDS:

Front Chain Guards – Three Section Mower

Rear Chain Guards – Three Section Mower

DOUBLE CHAIN GUARDS:

Front Double Chain Guards Complete

Rear Double Chain Guards Complete