



HT3

- For Tractors 15 to 25 HP

Light duty rotary tiller, the HT3 is sturdy and versatile, can work in any kind of soil in most variable conditions.

STANDARD EQUIPMENT:

- 3 Point linkage Cat. I
- Offset front brackets
- Greaseable chain drive
- Depth adjustment through side skids
- Curved (Standard) or square blades (Available)
- Standing jack
- Shear pin drive line



HT4

- For Tractors 35 to 55 HP

Mid-light duty rotary tiller, the HT4 is sturdy and versatile, can work in any kind of soil in most variable conditions.

STANDARD EQUIPMENT:

- 3 Point linkage cat. 1
- Offset front brackets
- Oil bath oversized chain drive
- Depth adjustment through side skids
- Curved (Standard) or square blades (Available)
- Standing Jack
- Slip clutch drive line



HT6

- For Tractors 35 to 65 HP

Medium duty rotary tiller, able to work any kind of soil, with little power absorption.

STANDARD EQUIPMENT:

- 3-point linkage 1st Cat.
- Oil bath oversize chain drive
- Depth adjustment through skids
- Curved (Standard) or square blades (Available)
- Adjustable linkages
- Slip clutch drive line
- Offset front brackets

****PLEASE CONTACT LOCAL DEALER FOR MORE INFORMATION****



ROTARY TILLERS

HT3 HT4 HT6

HT3

15 TO 25 HP

MOD. ORDER NO	Cutting Width		Equipment Width		HP-CV-PS		N.	Shaft RPM	Spindle RPM	Max Cutting Depth		Weight		6	4
	cm.	inch.	cm.	inch.	MED.	MAX.				cm.	inch.	Kg.	lbs		
HT3-4215 40544	105	42	115	46	15-18	25	20	540	214	13	5	116	253	<input type="checkbox"/>	<input checked="" type="checkbox"/>
HT3-5018 40545	125	50	135	54	18-20	25	24	540	214	13	5	126	275	<input type="checkbox"/>	<input checked="" type="checkbox"/>

● Standard Equipment ★ On Request □ Not Available

HT4

35 TO 55 HP

MOD. ORDER NO	Cutting Width		Equipment Width		HP		N.	Shaft RPM	Spindle RPM	Max Cutting Depth		Weight		6	4
	cm.	inch.	cm.	inch.	MED.	MAX.				cm.	inch.	Kg.	lbs		
HT4-5834 40540	145	58	158	63	35-40	40	28	540	201	15	6	200	437	<input type="checkbox"/>	<input checked="" type="checkbox"/>
HT4-6435 40546	165	64	178	71	35-40	40	32	540	201	15	6	215	470	<input type="checkbox"/>	<input checked="" type="checkbox"/>

● Standard Equipment ★ On Request □ Not Available

HT6

35 TO 65 HP

MOD. ORDER NO	Cutting Width		Equipment Width		HP		N.		Shaft RPM	Max Cutting Depth		Weight	
	cm.	inch.	cm.	inch.	MED.	MAX.	6 ★	4 ●		cm.	inch.	Kg.	lbs
HT6-6640 40541	165	65	179	71	40-45	55	36	24	540	18	7	275	600
HT6-7445 40542	185	74	199	79	45-50	55	42	28	540	18	7	305	666

● Standard Equipment ★ On Request □ Not Available

4895 Red Bluff Road, Loris SC 29569
www.hardeebyevh.com

Phone: (843)756-2555 Fax: (843)756-4436
evhmfg@hardeebyevh.com